



















Symmetry range		Combinable units		
Reference	Power Input			
FW 209	2 x 2,5 kW	•		
FW 214	2 x 3,3 kW	•	•	
FW 218	2 x 5 kW	•	•	•
FW 222	2 x 6,5 kW	•	•	•
FW 224	2 x 7 kW	•	•	•
FW 236	2 x 8,8 kW		•	•

Bi-splits range		Circuit n.1			Circuit n.2		
Reference	Power Input						
FW 09-14	2,5 kW + 3,3 kW	•			•	•	
FW 09-18	2,5 kW + 5 kW	•			•	•	•
FW 09-22	2,5 kW + 6,5 kW	•			•		
FW 09-24	2,5 kW + 7 kW	•			•	•	•
FW 14-18	3,3 kW + 5 kW	•	•		•	•	•
FW 14-22	3,3 kW + 6,5 kW	•	•		•		
FW 14-24	3,3 kW + 7 kW	•	•		•	•	•
FW 18-22	5 kW + 6,5 kW	•	•	•	•		
FW 18-24	5 kW + 7 kW	•	•	•	•	•	•
FW 18-36	5 kW + 8,8 kW	•	•	•	•	•	•

Tri-splits range		Circuit n.1			Circuit n.2			Circuit n.3		
Reference	Power Input									
FW 309	3 x 2,5 kW	•			•			•		
FW 314	3 x 3,3 kW	•	•		•	•		•	•	
FW 318	3 x 5 kW	•	•	•	•	•	•	•	•	•
FW 09-214	2,5 kW + 2 x 3,3 kW	•			•	•		•	•	
FW 09-14-18	2,5 kW + 3,3 kW + 5 kW	•			•	•		•	•	•
FW 209-14	2 x 2,5 kW + 3,3 kW	•			•			•	•	
FW 209-18	2 x 2,5 kW + 5 kW	•			•			•	•	•

Reference	Cooling only Dimensions LxDxH (mm)	Heat pump dimensions LxDxH (mm)	Absorbed power (kW) <sup>(1)</sup>	Water Flow Cooling only (Wasted water) (l/h) <sup>(2)</sup>	Water Flow Cooling only (Water loop) (l/h) <sup>(3)</sup>
FW 209	800 x 380 x 630 (h)		1,8	212	354
FW 214			2,3	278	464
FW 218			3,1	422	704
FW 222	864 x 469 x 835 (h)	864 x 469 x 835 (h)	3,6	580	966
FW 224			3,6	580	966
FW 236			6,0	770	1284
FW 224-Y*			4,2	580	966
FW 236-Y*			5,8	752	1252
FW 09-14	800 x 380 x 630 (h)		2,1	245	409
FW 09-18	864 x 469 x 835 (h)		2,4	317	529
FW 09-22		2,7	396	660	
FW 09-24		2,7	396	660	

Reference	Cooling only Dimensions LxDxH (mm)	Heat pump dimensions LxDxH (mm)	Absorbed power (kW) <sup>(1)</sup>	Water Flow Cooling only (Wasted water) (l/h) <sup>(2)</sup>	Water Flow Cooling only (Water loop) (l/h) <sup>(3)</sup>		
FW 14-18	864 x 469 x 835 (h)		2,7	350	584		
FW 14-22			3,0	429	715		
FW 14-24			3,0	429	715		
FW 18-22			3,4	501	835		
FW 18-24			3,4	501	835		
FW 18-36			4,5	596	994		
FW 309			864 x 469 x 835 (h)		2,6	318	531
FW 314					3,5	417	696
FW 318					4,7	633	1056
FW 09-214			1120 x 630 x 450 (h)		3,2	384	641
FW 09-14-18	3,6	456			761		
FW 209-14	2,9	351			586		
FW 209-18	3,3	423			706		

Function limits		Inside temperature	Outside temperature
Cooling only	Mini	19°C TS / 14°C TH	19°C TS <sup>(1)</sup>
	Maxi	35°C TS / 24°C TH	40°C TS
Heat pump	Mini	-	-10°C TS
	Maxi	27°C TS	24°C TS / 18°C TH

- (1) : Heat pump mode  
 (2) : Wasted water temperature : Intake at +15°C and discharge at +35°C  
 (3) : Water loop temperature : Intake at +25°C and discharge at +30°C

Maximum length	20 m
Maximum Variation (l)	5 m

(l) : Equivalent length 20 m

DB: Dry Bulb - WB: Wet bulb (l) Can function at lower temperatures condensation regulation kit available in option.  
 Measuring conditions : Inside Air Temperature (27°C DB/19°C WB - Outside Air Temperature : 35°C DB/24°C WB)  
 Inside Air Temperature (20°C DB/15°C WB - Outside Air Temperature : 7°C DB/6°C WB)